

## **PANORAMA - Details**

### **CONSTRUCTION**

Demountable, frameless, single or double glazed partition wall without vertical uprights.

### **DIMENSIONS**

Height: up to 3,100 mm, other sizes in height or width upon request

Width: Solid elements 900/1,200 mm, Glass elements 900/1,200 mm

### **STRUCTURE**

10 and / or 12 mm toughened safety glass (ESG)

or laminated safety glass (VSG)

19 mm melamine / veneer-coated chipboard panels

### **TOLERANCES**

Ground +/- 13 mm

Ceiling +/- 13 mm

### **MATERIALS**

Supports / stands: steel profiles, 2 x 0.8 mm compressed clamping screw

Surfaces: steel, galvanized, 0.8 mm by 12.5 mm

Inner filler: mineral wool

Floor and ceiling U-profiles: 1.5 mm galvanized steel profiles

### **SOUND ABSORPTION**

Rw = up to 47 dB laboratory value

### **DOOR ELEMENTS**

Door frame: aluminum frame with 3 hinges

Door leaves: wide range of doors, from 40 mm to 100 mm

### **CONNECTION**

Zero joint or 5 mm joint for massive modules

Glass panels are connected with transparent silicone tape, polyethylene terephthalate or polycarbonate profiles

## **ATTACHEMENTS**

Integrated power supply

Ventilation bars, air conditioning panels

Soundproofing panels

Cabinets, shelving systems

Dynamic lighting

Multimedia

Panels covered with textiles

Privacy glass