

## **STRING<sup>2</sup> - Details**

### **CONSTRUCTION**

Removable partition wall clad with steel and / or chipboard.

### **CONSTRUCTION HEIGHT**

up to 8,000 mm

### **DIMENSIONS**

Height: up to 3,100 mm

Width: Solid elements 900/1,200 mm, glass elements 900/1,200 mm

### **WALL THICKNESS**

100 mm

Double-glazed panels in 4, 6 or 8 mm thickness

In monoblock or biblock aluminum profiles

### **TOLERANCES**

Ground +/- 13 mm

Ceiling +/- 13 mm

### **MATERIALS**

0.8 mm galvanized steel on 12.5 mm plasterboard

19 mm chipboard (melamine or veneer)

single, - or double glazed Flush glazing (structural glazing)

Fabric-related steel panels

### **SOUND ABSORPTION**

Solid wall  $R_w$  41 – 50 dB laboratory value

Glass wall  $R_w$  41 – 48 dB laboratory value

### **DOOR ELEMENTS**

Door frame: aluminum or steel, frame with 3 hinges

Door leaves: wide range of doors, from 40 mm to 100 mm

## **CONNECTION**

Zero joint or 5 mm shadow joint

All elements are tightened by tension screws

## **ATTACHEMENTS**

Integrated power supply

Ventilation bars, air conditioning panels

Soundproofing panels

Cabinets, shelving systems

Dynamic lighting

Multimedia

Panels covered with textiles

Privacy glass, blinds