#### **VISTA DUO - Details**

### CONSTRUCTION

Movable partition wall system in aluminum construction as a standless, 2-shell all-glass construction with filigree floor and ceiling profiles, without support profiles.

### **CONSTRUCTION HEIGHT**

Max. height 3,200 mm

Unlimited wall length

### **WALL THICKNESS**

100 mm

Door frame profile and door side part 58 mm

### **SURFACE**

Max. 3 m<sup>2</sup> glass surface can be realized without glass joint

# **SOUND ABSORPTION**

0mm ESG/ 12mm ESG RwP = 42 dB

10mm ESG/ 10mm VSG Si RwP = 43 dB

10mm ESG/ 12mm VSG Si RwP = 44 dB

12mm ESG/ 12mm VSG Si RwP = 45 dB

Vista Duo door RwP = 45 dB

Door element with wooden door RwP = bis 36 dB

Aluminum tubular frame door = RwP = bis 38 dB

All-glass door RwP = bis 33 dB

### **DOOR ELEMENTS**

Door frame: aluminum frame, double or single rebate

With 3-dimensional adjustable belt substructure

Door leaves: flush glazing, closed surface, plain or wood decor, frameless all-glass door leaf, aluminum tubular frame door leaf, wooden door leaf, sliding door construction

### **EXECUTION**

A 1-part or 2-part connection profiles, uniform height of 45 mm

Butt jointed without profile, glass connection with a passivated, recessed pure acrylate dry seal, joint width 2 mm with polished, butt jointed glass edges

Door frames, floor, ceiling and wall connection profiles made from extruded aluminum profiles

# **ATTACHEMENTS**

Installation of switches and sockets in special aluminum door side panel, width 125 mm Installation of electrical horizontal blinds in the space between the panes possible